


AR DOKU DOLU 3 LAYER Laminated fabrics



Woven fabric
TPU Membrane
Knit fabric



Rain Protection

EN 343



High Visibility

EN 20471



1975
ARITEKS
FUNCTIONAL TECHNICAL FABRICS

Phone: +90 212 538 05 98

Fax: +90 212 537 08 46

E-Mail: support@ariteksinfo.com

Web: www.ariteks.net




Ariteks, founded as a family owned business in 1975, is the leading textile manufacturer company both in fashion and technical textiles.

By continuously developing high-end technologies it provides solutions to end users in apparel, protective workwear, functional sport, medical wear as well as technical textiles in construction and transportation industries.





As the pioneer company in special dyeing methods like indigo, vat, space-dye, coating and laminating systems, Ariteks produces highest-quality fabrics both for international and domestic markets.

Ariteks uses clean and renewable energy resources. It consumes minimum amount of water by using continuous optimised systems.

Based in 14000m² with 12 separate in house R&D laboratories, the company spends 5% of its budget for research and developing future technologies. It focuses especially on 3rd generation solar cells on flexible fabrics and biosensing textiles.



CONTENT

1	ArDoku	300 gr/m ² , 84% Polyester 10% Pu 6% Elastane, 3 layer laminated, Softshell Fabric	 	4-5
2	ArDolu	210 gr/m ² , 95% Polyester 5% Elastane, 3 layer laminated, Bonded Fabric	 	6-7



300 gr/m², 84% Polyester
10% Pu 6% Elastane,
3 layer laminated,
Softshell Fabric



Sample



ArDoku - 5651 Turquoise**ArDoku - 5647 White****ArDoku - 5616 Green****ArDoku - 5613 Black****ArDoku - 5612 Dark Red****ArDoku - 5611 Navy****ArDoku - 5610 Sax****ArDoku - 5514 Grey****ArDoku - 5515
High Visible Yellow****ArDoku - 5516
High Visible Orange**

Description

ArDoku is 84% polyester 10% pu 6% elastane softshell fabric. The top layer is elastic woven fabric, the middle layer is breathable tpu membrane, and the last layer is polar fabric.

The basic usage is for winter jackets.

ArDoku is certified for EN 343 and EN 20471.

Technical Parameters

Name	Values	Standards
Fiber	84% Polyester (PES) 10% Polyurethane (PU) 6% Elastane (EL)	EN ISO 2076
Yarn	75 Denier	EN ISO 2060
Weight	300 ±10 gr/m ²	EN ISO 3081
Width	1500 ±20 mm	EN ISO 3932
Tensile Strength	Warp>1000N; Weft>800N	EN ISO 13934-1
Tear Strength	Warp>40N; Weft>35N	EN ISO 13937-2
Dimensional Change	-3%<Length<+3%;-3%<Width<+3%	EN ISO 5077
Rubbing Fastness	4-5	EN ISO 105 X12
Perspiration Fastness	4-5	EN ISO 105 E04
Washing Fastness	4-5	EN ISO 105 C06
Dry Cleaning Fastness	4-5	EN ISO 105 D01
Hypochlorite Fastness	4-5	EN ISO 105 N01
Hot Press Fastness	4-5	EN ISO 105 X11
pH	4,0 - 7,5	EN ISO 3071
Azo Test	No Azo Colorants.	EN ISO 14362-1
Application	Winter Jackets	
Quality Management	Done	ISO 9001
Waterproof	Class 3,3	EN 343
High Visible	Yes	EN 20471




210 gr/m², 95% Polyester
5% Elastane, 3 layer laminated,
Bonded Fabric



Sample



ArDolu - 5368 Black**ArDolu - 5367 Navy****ArDolu - 5383
High Visible Green****ArDolu - 5385
High Visible Orange**

The technical data on this guide is given for information and correct at the time of design. It can be changed without prior notice.

Description

ArDolu is 95% polyester 5% pu bonded fabric. The top layer is woven fabric, the middle layer is breathable tpu membrane, and the last layer is knit fabric. The basic usage is for winter parka and raincoats. ArDolu is certified for EN 343 and EN 20471.

























Technical Parameters

Name	Values	Standards
Fiber	95% Polyester (PES) 5% Polyurethane (PU)	EN ISO 2076
Yarn	75 Denier	EN ISO 2060
Weight	210 ±10 gr/m ²	EN ISO 3081
Width	1500 ±20 mm	EN ISO 3932
Tensile Strength	Warp>1000N; Weft>800N	EN ISO 13934-1
Tear Strength	Warp>40N; Weft>35N	EN ISO 13937-2
Dimensional Change	-3%<Length<+3%;-3%<Width<+3%	EN ISO 5077
Rubbing Fastness	4-5	EN ISO 105 X12
Perspiration Fastness	4-5	EN ISO 105 E04
Washing Fastness	4-5	EN ISO 105 C06
Dry Cleaning Fastness	4-5	EN ISO 105 D01
Hypochlorite Fastness	4-5	EN ISO 105 N01
Hot Press Fastness	4-5	EN ISO 105 X11
pH	4,0 - 7,5	EN ISO 3071
Azo Test	No Azo Colorants.	EN ISO 14362-1
Application	Raincoat	
Quality Management	Done	ISO 9001
Waterproof	Class 3,3	EN 343
High Visible	Yes	EN 20471

Fashion Fabrics



Technical Fabrics

  BUILDING	  HOME	  PROTECTION	  MEDICAL	  SPORT	  TRANSPORT
  GEOLOGY	  PACKAGE	  CLOTH	  AGRICULTURE	  ENVIRONMENT	  MACHINE

Ariteks Fabric Factory
 Address: Velimese OSB Mah.210.Sokak,
 No:9/8 59930, Ergene Tekirdag/Turkey
 Phone: +90 282 676 41 90
 Fax: +90 282 676 46 13
 E-Mail: support@aritekinfo.com
 Web: www.aritek.net